

Large corrected grain leather with a pigmented finish and prominent two tone gloss appearance.
(Hide size av.4.5sqm, thickness ca. 1.0mm)

| | |
|---|--|
| Applications | Suitable for residential, contract. |
| Natural Leather | Leather is a natural product and the uniqueness of each hide is identified on occasion by growth marks, scars, variations in grain and other natural characteristics which add to the beauty of real leather and should not be regarded as a defect. Due to the natural properties of leather, colour and texture variations between batches may occur. |
| Care Information | <ul style="list-style-type: none"> ✓ Wipe away stains with a soft damp cloth as soon as they occur. ✓ In depth clean with mild lukewarm soapy water taking care not to soak the leather (soap flakes should be used), this prevents dirt build up. ✓ Dust with a soft cloth and Vacuum frequently. ✓ Futura cleaners and conditioners are available to help maintain this type of leather. |
| Precautions Protect from / Avoid | <ul style="list-style-type: none"> ✗ Sources of excessive heat, i.e. fires or close to radiators ✗ Direct sunlight particularly on aniline and semi aniline types ✗ Furniture polishes and waxes ✗ Household detergents and solvents |
| Characteristics and Test Methods | Manufactured under the ISO9001:2008 quality system and to comply with British / European standards for upholstery leather and the furnishings fire safety regulations 1988. |

| Characteristic | Method | Recommended Values |
|--|---------------------------------------|------------------------|
| Fastness to Rubbing 500 dry | EN ISO 11640 EN ISO 11641 | min 4 grey scale |
| Fastness to Rubbing 250 wet | | min 3/4 grey scale |
| Fastness to Rubbing 80 alkaline ph8 | | min 3/4 grey scale |
| Flexing Endurance | EN ISO 5402 | 50,000 |
| Tear Strength | EN ISO 3377-1 | ≥ 20 N |
| Surface Adhesion | EN ISO 11644 | 2N/10mm (min) |
| Colour Fastness to Light | EN ISO 105-B02 | Min 5 blue scale |
| Fire Resistance - Domestic | BS5852:part 1 ign. source 0 cigarette | Pass |
| Fire Resistance - Domestic | BS5852:part 1 ign. source 1 match | Pass |
| FR – Contract (specify requirement on order) | BS5852 Crib/Source 5 | Pass (after treatment) |

All our leathers comply with strict regulations and EU directives covering the use and presence of PCP, CFC, ChromoVI, Dimethylfumarate (DMF) and Azo dyestuffs during the tanning process.